

LCD Modular Energy meters at 100A direct input

- Active
- Active & Reactive



TYPE	CERTIFICABLE ACTIVE ENERGY	CERTIFICABLE ACTIVE & REACTIVE ENERGY	PROGRAMMABLE ACTIVE & REACTIVE ENERGY
OVERALL DIMENSIONS (mm or DIN modules)	6 DIN	6 DIN	6 DIN
DISPLAY	LCD 2 Rows	LCD 2 Rows	LCD 2 Rows
INPUTS	230V; 400V - 100A direct		
ADDITIONAL VARIABLES	W, Wmed, Wmax, cosfi	W, VAr, Wmed, VArmed, Wmax, VArmax, cosfi	
ACCURACY CLASS	2%	2-3%	
AUX. SUPPLY VOLTAGE	SELF-SUPPLIED (115 VAC or 230 VAC on demand)		

SINGLE PHASE

CODE	C15WSL100	C15QSL100	C15USL100
PRICE			

3 PHASE, 4 WIRES, UNBALANCED LOAD

CODE	C15WTL100	C15QTL100	C15UPL100
PRICE			

SPECIAL EXECUTIONS EXTRAPRICES

RS485 MODBUS RTU & JBUS PROTOCOL
PROFIBUS DP V0			
ETHERNET / MODBUS TCP			
JOHNSON N2 OPEN			☎
ACCURACY CLASS 1% (Wh), 2% (VARh)
OPERATING FREQUENCY 400Hz
PHOTO-MOS PULSE OUTPUT (max. 250V 100mA)	(2 outputs)
IP54 PROTECTION DEGREE (FRONT SIDE)
IP55 PROTECTION DEGREE (FRONT SIDE)
BIDIRECTIONAL VERSION	●
DUAL RATE VERSION		
AUX. SUPPLY VOLTAGE 24 or 48 or 400 V AC
AUX. SUPPLY VOLTAGE 24 or 48 or 110 V DC
AUX. SUPPLY VOLTAGE 220 V DC
AUX. SUPPLY VOLTAGE 20+60V AC/DC
AUX. SUPPLY VOLTAGE 80+260V AC/DC
TROPICALIZATION
SHIP MOUNTING