

Modular Energy meters

- Active
- Reactive
- Active & Reactive



TYPE	ACTIVE ENERGY	REACTIVE ENERGY	ACTIVE & REACTIVE ENERGY
OVERALL DIMENSIONS (mm or DIN modules)	6 DIN	6 DIN	6 DIN
DISPLAY	Electro-mechanical 7 digits (h 4mm)	Electro-mechanical 7 digits (h 4mm)	2x Electro-mechanical 7 digits (h 4mm)
INPUTS	100: $\sqrt{3}V$; 110: $\sqrt{3}V$; 100V; 110V; 230V; 400V - Rated voltage or VT ratio to be specified 1+5A - Rated current or CT ratio to be specified		
ACCURACY CLASS	2%	3%	2-3%
AUX. SUPPLY VOLTAGE	SELF-SUPPLIED (115 VAC or 230 VAC on demand)		

SINGLE PHASE

CODE	C15WS	C15RS	C15QS
PRICE			
SEALABLE VERSION (extraprice)

3 PHASE, 3 WIRES, BALANCED LOAD

CODE	C15WY	C15RY	C15QY
PRICE			

3 PHASE, 4 WIRES, BALANCED LOAD

CODE	C15WN	C15RN	C15QN
PRICE			

3 PHASE, 3 WIRES, UNBALANCED LOAD

CODE	C15WD	C15RD	C15QD
PRICE			
SEALABLE VERSION (extraprice)

3 PHASE, 4 WIRES, UNBALANCED LOAD

CODE	C15WT	C15RT	C15QT
PRICE			
SEALABLE VERSION (extraprice)

3 PHASE, 3 or 4 WIRES, BALANCED LOAD (400V 5A CT ratio programmable)

CODE	C15WP		
PRICE			

SPECIAL EXECUTIONS EXTRAPRICES

ACCURACY CLASS 1% (Wh), 2% (VARh)
OPERATING FREQUENCY 400Hz
PHOTO-MOS PULSE OUTPUT (max. 250V 100mA)	(2 outputs)
IP54 PROTECTION DEGREE (FRONT SIDE)			
IP55 PROTECTION DEGREE (FRONT SIDE)			
BIDIRECTIONAL VERSION (2 display)	
DUAL RATE VERSION (2 display)		
AUX. SUPPLY VOLTAGE 24 or 48 or 400 V AC
AUX. SUPPLY VOLTAGE 24 or 48 or 110 V DC
AUX. SUPPLY VOLTAGE 220 V DC
AUX. SUPPLY VOLTAGE 20+60V AC/DC
AUX. SUPPLY VOLTAGE 80+260V AC/DC
TROPICALIZATION
SHIP MOUNTING