

Digital meters

48 x 24 mm



FRONT SIZE (mm)		48 x 24		48 x 24		
DISPLAY DIGITS		3		3 ½		
MAX. DISPLAY VALUE		999		1999		
AUX. SUPPLY VOLTAGE		12 o 24 o 48 VDC (Insulation at 700V)		12 o 24 o 48 VDC (Insulation at 700V)		
MEASURING TYPE		INPUTS	CODE	PRICE	CODE	PRICE
AC	mA - A	100mA ÷ 10A	D44EAXXXX3		D44EAXXXX5	
	V	1 ÷ 600V	D44EVXXX3		D44EVXXX5	
AC TRMS	mA - A (5...120% In)	100mA ÷ 10A	D44EARXXX3		D44EARXXX5	
	V (5...120% Vn)	1 ÷ 600V	D44EVRXXX3		D44EVRXXX5	
DC	µA - mA - A	± (100µA ÷ 10A)	D44MAXXXX3		D44MAXXXX5	
	mV - V	± (40mV ÷ 600V)	D44MVXXX3		D44MVXXX5	
Cosφ, Wca, Hz VAR, VA, Wcc, RPM, ecc...	Input from external accessory transducer (see page 4.14)	1mA	D44MMAXX301		D44MMAXX501	

SPECIAL EXECUTIONS EXTRAPRICES

M3 SCREW TERMINALS	●	●
PROGRAMMABLE DECIMAL POINT
AUX. SUPPLY VOLTAGE 12 or 24 or 48 or 115/230 or 400 V CA (Insulation at 2KV with external accessory)
AUX. SUPPLY VOLTAGE 24 or 48 or 110 V DC (Insulation at 2KV with external accessory)
AUX. SUPPLY VOLTAGE 220 V DC (Insulation at 2KV with external accessory)
AUX. SUPPLY VOLTAGE 20÷60V AC/DC (Insulation at 2KV with external accessory)
AUX. SUPPLY VOLTAGE 80÷260V AC/DC (Insulation at 2KV with external accessory)
IP54 PROTECTION DEGREE (FRONT SIDE)
IP55 PROTECTION DEGREE (FRONT SIDE)
TROPICALIZATION
SHIP MOUNTING
VERSION FROM H ₂ S, NH ₃ APPLICATIONS	☎	☎