








- Plugs and socket-outlets with an integral switching device (IEC/EN 60309-1 and 60309-4)
- Easy handling by a simple press on the socket latch
- Very compact design
- Casings made of glass fibre reinforced polyester
- Resistance to shocks, UV radiation, chemical agents...
- Resistance to high pressure washing
- Interior keying system with 24 non-interchangeable positions
- Silver-nickel butt contacts – not affected by oxidation
- Safety shutter










Decontactors









16 A – 63 A
Up to 1000 V AC and 250 V DC
IP66/IP67

Basic components

Socket-outlet	A / V	Contacts	Part N°	
	16–20 A / 230 V	1P + N + E	61 14015	+  = 
	16–20 A / 400 V	3P + N + E	61 14017	
	32 A / 230 V	1P + N + E	61 34015	
	32 A / 400 V	3P + N + E	61 34017	+  = 
	32 A / 400 V	3P + N + E + 2 aux.	61 34017 972	
	63 A / 230 V	1P + N + E	61 64015	
	63 A / 400 V	3P + N + E	61 64017	+  = 
	63 A / 400 V	3P + N + E + 2 aux.	61 64017 972	
	63 A / 400 V	3P + N + E + 4 aux.	61 64017 264	
	For additional voltages (up to 1000 V), other contact configurations or options, please consult us.			

Inlet	A / V	Contacts	Part N°	
	16–20 A / 230 V	1P + N + E	61 18015	+  = 
	16–20 A / 400 V	3P + N + E	61 18017	
	32 A / 230 V	1P + N + E	61 38015	
	32 A / 400 V	3P + N + E	61 38017	+  = 
	32 A / 400 V	3P + N + E + 2 aux.	61 38017 972	
	63 A / 230 V	1P + N + E	61 68015	
	63 A / 400 V	3P + N + E	61 68017	+  = 
	63 A / 400 V	3P + N + E + 2 aux.	61 68017 972	
	63 A / 400 V	3P + N + E + 4 aux.	61 68017 264	
	For additional voltages (up to 1000 V), other contact configurations or options, please consult us.			

Installation accessories

Wall box 30°, poly	Size	/ Entry	Part N°	Modular wall box 70°, poly	Size	Part N°	Wall box metal + metal sleeve 70°	Size	/ Entry	Part N°
	for 16–20 A	/ M20	61 1A053		for 16–20 A	51 AA058		for 63 A	/ M32	87 3A053 419
	for 32 A	/ M25	61 3A083		for 32 A	51 BA058				
	for 63 A	/ M25	61 6A053		for 63 A	51 CA058				
Inclined sleeve 30°, poly	Size	Part N°	Modular inclined sleeve 70°, poly	Size	Part N°	Inclined sleeve 70°, metal	Size	Part N°		
	for 16–20 A	61 1A027		for 16–20 A	51 AA757		for 63 A	87 3A087		
	for 32 A	61 3A027		for 32 A	51 BA757					
	for 63 A	61 6A027		for 63 A	51 CA757					
Standard handle	Size	/ Ø mm	Part N°	Flowerpot handle	Size	/ Entry	Part N°			
	for 16–20 A	/ 9–18	61 1A013		for 16–20 A	/ M25	61 1A253 25P			
	for 32 A	/ 5–21	61 3A013		for 32 A	/ M25	61 3A253 25P			
	for 63 A	/ 10–30	61 6A473		for 63 A	/ M32	61 6A253 32P			

	Max. current / max. voltage		Load breaking capacity					
	400 V	500 V	690 V	Max. conductor cross-section in mm ²				
				flexible	stranded	auxiliaries		
DSN1	20 A	500 V	20 A	20 A	–	2,5	4	–
DSN3	32 A	690 V	32 A	32 A	32 A	6	10	6
DSN6	63 A	1000 V	63 A	63 A	63 A	16	25	2,5

Other currents / voltages on request.