

- Plugs and socket-outlets with an integral switching device (IEC/EN 60309-1 and 60309-4)
- Easy handling by a simple press on the socket latch
- No load-breaking capacity for 400 A or 1000 V versions
- Electrical and mechanical interlocking for 400 A or 1000 V versions
- Silver-nickel butt contacts – not affected by oxidation
- Robust metal casings (IK09)
- Wall box 20° made of stainless steel V2A
- Safety shutter
- Easy closing mechanism
- EMC versions on request



# Decontactors & Plugs & socket-outlets

250 A – 400 A  
Up to 1000 V AC and 1500 V DC  
IP54 – IP67

## Basic components

Socket-outlet	A / V	Contacts	Part N°	
	250 A / 1000 V	3P + E + 2 aux.	39 24223 172 099	 Wall box = Wall mounting socket  Inclined sleeve = Inclined socket  Handle = Connector
	250 A / 400 V	3P + N + E	39 24017	
	250 A / 400 V	3P + N + E + 2 aux.	39 24017 972	
	400 A / 400 V	3P + E + 2 aux.	39 44013 172 00N	
	400 A / 1000 V	3P + E + 2 aux.	39 44223 172 00N	
For additional voltages or other contact configurations, please consult us.				
Inlet	A / V	Contacts	Part N°	
	250 A / 1000 V	3P + E + 2 aux.	39 28223 172 099	 Wall box = Wall mounting appliance inlet  Inclined sleeve = Inclined appliance inlet  Handle = Plug
	250 A / 400 V	3P + N + E	39 28017	
	250 A / 400 V	3P + N + E + 2 aux.	39 28017 972	
	400 A / 400 V	3P + E + 2 aux.	39 48013 172 00N	
	400 A / 1000 V	3P + E + 2 aux.	39 48223 172 00N	
For additional voltages or other contact configurations, please consult us.				

## Installation accessories

Wall box 60°, metal			Wall box 20°, stainless steel V2A			(*) Replace XXX with the appropriate suffix number that represents the cable outer diameter of your choice: 35–46 mm → 63M 46–60 mm → 25Z 58–65 mm → 30Z
Size	/ Entry	Part N°	Size	/ Ø mm	Part N°	
	for 250 A	/ M63	39 2A053 63M	for 250 A / 36–65 for 400 A / 36–65	39 4A025 XXX(*) 39 4A025 XXX(*)	
Inclined sleeve 60°, metal			Surface mounting socket-outlet DS4			
Size	Part N°		A / V	Contacts	Ø mm	Part N°
	for 250 A for 400 A	39 2A027 39 4A027 68	400 A / 400 V 400 A / 1000 V	3P + E + 2 aux. 3P + E + 2 aux.	41–54 41–54	39 40013 CCC 826 39 40223 CCC 826
Equipped with contactor, on/off push-button, emergency push button						
Handle, poly			Handle, metal			(*) Replace XX with the appropriate suffix number that represents the cable outer diameter of your choice: 53–57 mm → 57      62–68 mm → 68 58–62 mm → 62      69–73 mm → 73
Size	/ Ø mm	Part N°	Size	/ Ø mm	Part N°	
	for 250 A	/ 34–44	39 2A753	for 250 A / 40–54 for 400 A / 53–73	39 2A915 39 4A915 XX(*)	

Max. current / max. voltage			Load breaking capacity					
			Max. conductor cross-section in mm <sup>2</sup>					
			400 V	500 V	690 V	flexible	stranded	auxiliaries
DS2	250 A	1000 V	250 A	200 A	200 A	95	120	1,5
DS4	400 A	1000 V	–	–	–	150	185	1,5