



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION
IEC Certification Scheme for Explosive Atmospheres
for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: issue No.:

Status:

Date of Issue: **2011-05-27** Page 1 of 4

Applicant: **BEKA associated Limited**
Old Charlton Road
Hitchin
Herts
SG5 2DA
United Kingdom

Electrical Apparatus: **4 and 5 Digit Field Mounting Indicators and Rate Totaliser**
Optional accessory:

Type of Protection: **Ex nA, Ex ic, Ex tc**

Marking: **IECEX ITS 11.0016**
Ex nA ic IIC T5 Gc
-40°C < Ta < +70°C
Ex tc IIIC T80°C Dc IP66
-40°C < Ta < +70°C

Approved for issue on behalf of the IECEx Certification Body: **A T Austin**

Position: **Certification Officer**

Signature:
(for printed version)

Date:

2011-05-27

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Intertek Testing & Certification Limited
ITS House, Cleeve Road,
Leatherhead,
Surrey, KT22 7SB
United Kingdom





IECEx Certificate of Conformity

Certificate No.: IECEx ITS 11.0016
Date of Issue: 2011-05-27 Issue No.: 0
Page 2 of 4

Manufacturer: **BEKA associates Limited**
Old Charlton Road
Hitchin
Herts
SG5 2DA
United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

- IEC 60079-0 : 2007-10** Explosive atmospheres - Part 0: Equipment - General requirements
Edition: 5
- IEC 60079-11 : 2006** Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"
Edition: 5
- IEC 60079-15 : 2010** Explosive atmospheres - Part 15: Equipment protection by type of protection "n"
Edition: 4
- IEC 60079-31 : 2008** Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Edition: 1

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

GB/ITS/ExTR11.0018/00

Quality Assessment Report:

GB/ITS/QAR06.0002/01



IECEx Certificate of Conformity

Certificate No.: IECEx ITS 11.0016

Date of Issue: 2011-05-27

Issue No.: 0

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The 4 and 5 Digit Field Mounting Indicators and Rate Totaliser are field mounted loop powered equipment designed to display a measured variable in meaningful engineering units within the hazardous area. The zero and span of the display are independently adjustable allowing the indicator to be calibrated to display a linear variable represented by the 4/20 mA signal.

A root extractor and an adjustable sixteen segment lineariser enable the indicator to display flow and non-linear variables such as tank level in engineering units.

The 4 and 5 Digit Field Mounting Indicators and Rate Totaliser may be one of the following;

BA304NE 4 Digit Indicator

BA324NE 5 Digit Indicator

BA354NE Rate Totaliser

The 4 and 5 Digit Field Mounting Indicator and Rate Totaliser may optionally incorporate Alarm circuit on the main display board and may additionally be fitted with an optional Backlight board.

The 4 and 5 Digit Field Mounting Indicators and Rate Totaliser comprise a field terminal board, a main display board, and an optional Backlight board, all housed within a plastic, glass reinforced polyester, enclosure. The enclosure provides a degree of protection IP66 (Gas/Dust).

CONDITIONS OF CERTIFICATION: NO

--



IECEx Certificate of Conformity

Certificate No.: IECEx ITS 11.0016

Date of Issue: 2011-05-27

Issue No.: 0

Page 4 of 4

EQUIPMENT(continued):

The maximum input parameters are:

TB1 4/20 mA Loop Input - Terminals 1 & 3:

$I_i = 100 \text{ mA}$

TB2 Backlight - Terminals 12 & 13 (4/20 mA loop powered):

$I_i = 100 \text{ mA}$ (connected in series with TB1 terminals 1 & 3)

TB2 Backlight - Terminals 12 & 14 (Separately powered):

$U_i = 30 \text{ V}$

TB3 Rate Totaliser - Terminals RS1 & RS2:

$U_i = 4.3 \text{ V}$

TB4 Alarms - each channel - Terminals 8 & 9; 10 & 11:

$U_i = 30 \text{ V}$

$I_i = 200 \text{ mA}$