



The **BA444DF-F FOUNDATION™ fieldbus Indicator** is an intrinsically safe instrument that can display up to eight fieldbus process variables within a hazardous area. A numeric annunciator on the left hand side of the screen shows which variable is being displayed. This version of the indicator supports FOUNDATION™ fieldbus protocol; for PROFIBUS PA systems an alternative version is available – please see the BA444DF-P PROFIBUS datasheet.

**Configuration as a fieldbus Node or Listener** allows the indicator to be tailored to suit local requirements. As a FOUNDATION™ fieldbus Node the indicator is configured by the fieldbus host and the displayed variable is selected from the eight pre-configured fieldbus variables using the indicator's push buttons. When configured as a Listener, the indicator is not visible to the fieldbus host; may not be subject to a Node Licence Fee and is configured and controlled by the indicator's push buttons.

The **liquid crystal display** has large 20mm high digits providing maximum contrast and a wide viewing angle, allowing the BA444DF-F indicator to be read easily in most lighting conditions. The five digits, with four decimal points and a negative sign, may be configured to display any variable between -99999 and 99999. The 31 segment bargraph, which provides a bold analogue indication of the fieldbus variable, may be conditioned to any starting or finishing values within the fieldbus variable's range.

The **enclosure** which is moulded in glass reinforced Polyester (GRP) has stainless steel fittings, silicone gaskets and an armoured glass window. Its robust construction provides IP66 protection which has been independently assessed by Intertek Testing Services. A separate

terminal compartment allows the instrument to be installed and terminated without exposing the indicator electronics. To further simplify wiring and subsequent inspection, the terminal cable entries and clamping screws are forward facing. The indicator may also be mounted onto a vertical or horizontal pipe using one of the accessory kits.

**ATEX intrinsic safety certification** allows the BA444DF-F to be installed in all gas hazardous areas. The two fieldbus terminals comply with the Fieldbus Intrinsic Safety Concept FISCO simplifying system design and documentation. Separate entity input safety parameters also allow connection to most non-FISCO intrinsically safe systems. A BA444DF-F may therefore be connected to almost any intrinsically safe fieldbus segment that can supply an additional 13mA to power the instrument.

**FM, cFM and IECEx approvals** allow installation in the USA, Canada plus the many countries accepting international IECEx certificates. All approvals incorporate FISCO certification. Details of the versions available are shown in the How to Order section on the reverse of this datasheet.

**Units of measurement** and the instrument's application or tag number can be economically marked onto the display escutcheon prior to despatch or after installation on-site. Alternatively, for customers who prefer a stainless steel label, the indicator can be supplied with a removable blank or custom etched stainless steel plate mounted on the front of the enclosure.

**For panel mounting applications** see the BA448CF-F FOUNDATION™ fieldbus indicator datasheet. This instrument has a similar electrical specification but is housed in a 144 x 72 panel mounting enclosure.

# BA444DF-F

## FOUNDATION™ fieldbus Fieldbus Indicator

### 8 variables

*Intrinsically safe for use in gas and dust hazardous areas*

- ◆ Large 5 digit display with bargraph
- ◆ FOUNDATION™ fieldbus protocol
- ◆ Displays up to 8 fieldbus variables
- ◆ Selectable Node or Listener modes
- ◆ Intrinsically safe ATEX gas or ATEX gas & dust or FM, cFM & ATEX gas

All versions have IECEx certification

- ◆ Entity parameters & FISCO compliant
- ◆ IP66 field mounting GRP enclosure
- ◆ 3 year guarantee



# BEKA associates

BEKA associates Ltd. Old Charlton Rd. Hitchin, Hertfordshire, SG5 2DA, U.K. Tel. (01462) 438301 Fax (01462) 453971 e-mail sales@beka.co.uk www.beka.co.uk

