



The HEDI CableFix is the clever solution to tie up, suspend or carry cables, wires or hoses, for example.

The clever accessories:

HEDI CableFix.



The HEDI CableFix

| Art. no. | EAN | Locating band length | Loadability | Packing Unit (PU) | |
|----------|---------------|----------------------|--------------|-------------------|--|
| 9071S | 4003644013050 | 10 cm | up to 20 kg | 10 | |
| 9071L | 4003644013043 | 21 cm | up to 50 kg | 10 | |
| 9071XL | 4003644002856 | 30 cm | up to 100 kg | 10 | |

- Extremely rugged plastic hook
- Flexible rubber band with a loadability of up to 100 kg (depending on version)





Always the proper accessories:


Plugs, couplings and adapter cables, 250 V.

Schuko plug and socket

Rugged rubber version, black, for use at construction sites and in industry



| Art. no. | EAN | Description | Version |
|----------|---------------|---------------------------------|--|
| 9003 | 4003644008513 | Schuko coupling with lid, black | 250 V / 16 A, for cross-sections up to 3x2.5 mm ² |
| 9004 | 4003644008506 | Schuko plug black | 250 V / 16 A, for cross-sections up to 3x2.5 mm ² |



3-fold pendant coupling

Rugged rubber version, blue / black, for use at construction sites and in industry



| Art. no. | EAN | Description | Version |
|----------|---------------|--|--|
| 9061 | 4003644015689 | Schuko coupling, 3-fold with lids, black | 16 A / 250 V, for cross-sections up to 3x2.5 mm ² |



4-fold pendant coupling

Rugged plastic version, black, for use at construction sites and in industry



| Art. no. | EAN | Description | Version |
|----------|---------------|---|--|
| 9043 | 4003644015085 | Schuko coupling, 4-fold with hinged lids, black | 16 A / 250 V Cross-section max. 3 x 1.5 mm ² |




CEE plug and coupling

3x16 A / 250 V, rugged version for use at construction sites and in industry



| Art. no. | EAN | Description | Version | |
|----------|---------------|--|--|--|
| 9005 | 4003644008520 | CEE connector 3x16 A With twist quick-release fastener | 250 V / 16 A, for cross-sections up to 3x2.5 mm ² | |
| 9007 | 4003644008537 | CEE coupling 3x16 A with hinged lid and twist quick-release fastener | 250 V / 16 A, for cross-sections up to 3x2.5 mm ² | |




CEE adapter cable

3x16 A / 250 V, rugged version for use at construction sites and in industry



| Art. no. | EAN | Description | Version | |
|-----------|---------------|--|--------------------------------|--|
| AK-SS-CK | 4003644004546 | Input: Schuko Output: CEE 3x16 A | Length: 1.5 m H07RN-F 3G1.5 | |
| AK-SS-CK2 | 4003644002603 | Input: Schuko Output: CEE 3x16 A | Length: 1.5 m H07RN-F 3G2.5 | |
| AK-CS-SK | 4003644004515 | Input: CEE 3x16 A Output: Schuko | Length: 1.5 m H07RN-F 3G1.5 | |
| AK-CS-SK2 | 4003644002597 | Input: CEE 3x16 A Output: Earthing pin system | Length: 1.5 m H07RN-F 3G2.5 | |





Always the proper accessories:

Plugs, couplings and adapter plugs, 400 V.

CEE plug and coupling

5x16 A, 400 V, rugged version for use at construction sites and in industry, for cross-sections up to 5x4.0 mm²



| Art. no. | EAN | Description | Version |
|----------|---------------|---|---|
| 9006 | 4003644008544 | CEE connector 5x16 A With twist quick-release fastener | 16 A / 400 V, for cross-sections up to 5x4.0 mm ² |
| 9009 | 4003644019342 | Phase reversal plug CEE 5x16 A | 16 A / 400 V, for cross-sections up to 5x4.0 mm ² |
| 9008 | 4003644008551 | CEE coupling 5x16 A With twist quick-release fastener | 16 A / 400 V, for cross-sections up to 5x4.0 mm ² |




CEE plug and coupling

5x32 A, 400 V, rugged version for use at construction sites and in industry, for cross-sections up to 5x6.0 mm²



| Art. no. | EAN | Description | Version |
|----------|---------------|---|---|
| 9052 | 4003644008568 | CEE connector 5x32 A With twist quick-release fastener | 32 A / 400 V, for cross-sections up to 5x6.0 mm ² |
| 9010 | 4003644019359 | Phase reversal plug CEE 5x32 A | 32 A / 400 V, for cross-sections up to 5x6.0 mm ² |
| 9053 | 4003644008575 | CEE coupling 5x32 A With twist quick-release fastener | 32 A / 400 V, for cross-sections up to 5x6.0 mm ² |



CEE adapter plug

5x16 A / 5x32 A or 5x32 A / 5x16 A, rugged version for use at construction sites or in industry



| Art. no. | EAN | Description | Installed fuses |
|----------|---------------|---|-----------------|
| AK1632F | 4003644002122 | Input: CEE 5x16 A, 400 V, phase reverser Output: CEE 5x32 A, 400 V | – |
| AK3216F | 4003644002153 | Input: CEE 5x32 A, 400 V, phase reverser Output: CEE 5x16 A, 400 V | 3x C 16 A |



Reliable and safe:

Wall-mounted and flush-mounted sockets.



Wall-mounted sockets CEE with hinged lid

| Art. no. | EAN | Version | |
|----------|---------------|-------------------------|--|
| 9057 | 4003644015740 | CEE 5x16 A, 400 V | |
| 9058 | 4003644015757 | CEE 5x32 A, 400 V | |
| 9059 | 4003644015764 | CEE 5x63 A, 400 V, IP67 | |



Wall-mounted combination socket CEE with hinged lid

| Art. no. | EAN | Outputs | |
|----------|---------------|--|--|
| 97001 | 4003644019366 | 1 x CEE 5x16 A, 400 V 1 x Schuko, 250 V | |



Flush-mounted Schuko socket with hinged lid, blue

| Art. no. | EAN | Outputs | |
|----------|---------------|--------------|--|
| 9060 | 4003644015696 | 16 A / 250 V | |



Flush-mounted CEE socket 250 V with hinged lid, blue

| Art. no. | EAN | Version | |
|----------|---------------|----------------|--|
| 9054 | 4003644015702 | 3x16 A / 250 V | |



Flush-mounted CEE sockets 400 V with hinged lid, red

| Art. no. | EAN | Version | |
|----------|---------------|----------------|--|
| 9055 | 4003644015719 | 5x16 A / 400 V | |
| 9056 | 4003644015726 | 5x32 A / 400 V | |

